

Ceiling Finishes	
Key Value	Description
GS130MC01	600x600x1.5mm THK. NON-PERFORATED CLIP-IN ALUMINIUM CEILING WITH 1.5mm W-ANGLE TRIM POWDER COATED FINISH
GS130MC02	600x600x1.5mm THK. NON-PERFORATED LAY-ON ALUMINIUM CEILING WITH 1.5mm W-ANGLE TRIM POWDER COATED FINISH
GS130MC03	20x150x0.7mm THK. GALVANIZED STEEL BAFFLE CEILING WITH POWDER COAT FINISH AND AT 110mm/140mm SPACING, PERFORATED WITH ACOUSTIC FLEECE AND VOC FREE ANTI-MOULD ACRYLIC EMULSION PAINT ON-OFF FORM CONCRETE AND SERVICES ABOVE
GS130MC04	150x150x50mm EXTERNAL ALUMINIUM CELL CEILING WITH POWDER COATED FINISH AND VOC FREE ANTI-MOULD ACRYLIC EMULSION PAINT ON-OFF FORM CONCRETE AND SERVICES ABOVE
GS130MC05	600x600x1.5mm THK. NON-PERFORATED HOOK-ON ALUMINIUM CEILING WITH 1.5mm THK. W-ANGLE TRIM POWDER COATED FINISH WITH MOISTURE AND VAPOUR RESISTANCE
GS130MC07	275x2000x0.8mm THK. STORMPROOF NON-PERFORATED SUSPENDED ALUMINIUM CEILING PANEL SYSTEM WITH PVF2 COATING
GS130MC08	600x600x1.5mm THK. NON-PERFORATED AIR-TIGHT CLIP-IN ALUMINIUM CEILING "DURLUM" SYSTEM S1.12 WITH ANGLE TRIM POWDER COATED FINISH
GS130PB01	600x600x20mm THK. ACOUSTIC GLASSWOOL CEILING TILE WITH CONCEALED GRID AND SYMMETRICAL EDGE SYSTEM.
GS130TA01	16mm THK. MDF TIMBER ACOUSTIC CEILING PANEL SYSTEM "TOPAKUSTIK" TOPPERFO-T 16/16/10-2 (PERFORATED) WITH ECO FINISH AND GMS SUPPORTING FRAME
GS180TW02	100mm THICK INSULATION CEILING WITH 1.5mm THICK STAINLESS STEEL FINISH (SATIN)
GS180FR01	12mm THK. REINFORCED GYPSUM PLASTERBOARD CEILING AND INORGANIC SILICATE BASED MINERAL PAINT SYSTEM W/ GMS SUPPORTING FRAME
GS210EM04	INORGANIC SILICATE BASED MINERAL PAINT SYSTEM ON 10mm THK. INTERNAL PLASTER
GS210EM05	1 COAT OF LIQUID PREPOLYMER SEALING AND 2 FINISHING COATS OF WHITE ACRYLIC RESIN BASED COATING IN GLOSSY FINISH ON CEILING PLASTER TO CLP'S REQUIREMENT
GS210EP03	PROPRIETARY FIRE PROTECTION BOARD WITH 2 COATS OF VOC FREE ANTI-MOULD ACRYLIC EMULSION PAINT TO MEET FRR REQUIREMENT

Material Legend_Ceiling

1 : 200

Wall Finishes	
Key Value	Description
GS080FF02	FAIRFACE CONCRETE WITH SAW-CUT SURFACE FINISH
GS100GW01	235x19.5x13.5mm THK. UNGLAZED CERAMIC WALL TILE WITH TWO PENTAGONAL SHAPES (ONE WITH SYMMETRICAL SHAPE AND THE OTHER WITH NON-SYMMETRICAL SHAPE AND MIX TOGETHER) INCLUDING CORNER TILES ON 15mm THK. 1:3 C/S RENDER W/ APPROVED PROPRIETARY ADHESIVE SYSTEM
GS170AL11	2mm THK. ALUMINIUM SHEET ON 18mm THK. PLYWOOD BACKING
GS170BA02	2mm THK. BRONZE ANODIZED STAINLESS STEEL SHEET (GRADE 316) ON 18mm THK. PLYWOOD BACKING
GS170SS02	40x3mm THK. BRONZE ANODIZED STAINLESS STEEL FLAT BAR (GRADE 316)
GS180IW01	100mm THICK INSULATION WALL WITH 1.5mm THICK STAINLESS STEEL FINISH (SATIN) (GRADE 316)
GS180TA01	16mm THK. MDF TIMBER ACOUSTIC PANEL "TOPAKUSTIK" TOPPERFO-T 16/16/10-2 (PERFORATED) WITH OAK VENEER ECO FINISH FACING AND ASSOCIATED FRAMEWORK OVERALL THICKNESS 50mm
GS180TL03	97.75x97.75x5mm THK. "INAX" GLAZED CERAMIC WALL TILE "SPKC-100/M1001" WITH SIAA ANTI-BACTERIAL PROPERTY, INCLUDING ONE ROUND EDGE AND TWO ROUND EDGES TILES "SPKC-1060/M1001" AND "SPKC-1065/M1001" WITH ANTI-BACTERIAL PROPERTY
GS180TL10	600x600x10mm THK. HOMOGENEOUS TILE "ARIOSTEA" PIETRE NATURALI HIGH TECH SERIES (COLOUR: ARDESIA ANTRACITE, SEMI-MATT, SHADE VARIATION:V2) THROUGH BODY WITH "ACTIVE" ANTI-BACTERIAL PROPERTY ON C/S SCREED FIXING WITH APPROVED PROPRIETARY ADHESIVE SYSTEM AND POINTING WITH COLOURED GROUTING
GS180TL14	150x150x5.5mm THK. WHITE CERAMIC TILES DADO 1500mmH AND ONE COAT OF LIQUID PREPOLYMER SEALING
GS180TL50	1200x3600x3mm THK. "CEMAC" NEOLITH CLADDING PANEL IRON CORTEN SATIN FINISH WITH APPROVED PROPRIETARY ADHESIVE SYSTEM ON 18mm THK. PLYWOOD BACKING AND ASSOCIATED FRAMEWORK
GS180SD01	12mm THK. SOLID SURFACING MATERIAL ON 18mm THK. PLYWOOD BACKING
GS180LS01	1mm THK. LAMINATED PLASTIC SHEET FINISH ON 18mm THK. PLYWOOD BACKING
GS200TG02	6mm THK. BACK PAINTED TEMPERED GLASS ON 6mm THK. PLYWOOD BACKING
GS210EP05	15mm THK. INTERNAL PLASTER WITH INORGANIC SILICATE BASED MINERAL PAINT SYSTEM
GS210EP06	INORGANIC SILICATE BASED MINERAL PAINT SYSTEM ON 20mm THK. EXTERNAL RENDER

Material Legend_Wall

1 : 200

Skirting Finishes	
Key Value	Description
GS180TL07	1200x90x10mm THK. HOMOGENEOUS SKIRTING TILE "ARIOSTEA" PIETRE NATURALI HIGH TECH SERIES (COLOUR: ARDESIA ANTRACITE, SEMI-MATT, SHADE VARIATION:V2) THROUGH BODY WITH "ACTIVE" ANTI-BACTERIAL PROPERTY ON 1:3 C/S RENDER WITH APPROVED PROPRIETARY ADHESIVE SYSTEM AND POINTING WITH COLOURED GROUTING
GS180TL09	600x90x10mm THK. HOMOGENEOUS SKIRTING TILE "ARIOSTEA" PIETRE NATURALI HIGH TECH SERIES (COLOUR: BASALTO GRIGIO, MATT, SHADE VARIATION:V3) THROUGH BODY WITH "ACTIVE" ANTI-BACTERIAL PROPERTY ON 1:3 C/S RENDER WITH APPROVED PROPRIETARY ADHESIVE SYSTEM AND POINTING WITH COLOURED GROUTING
GS180TL12	300x100x12mm THK. COVERED QUARRY SKIRTING TILES ON 1:3 C/S RENDER
GS180VS03	4mm THK. CHEMICAL RESISTANT VINYL SHEET SKIRTING

* NOTE: DESCRIPTION OF THE REMAINING SKIRTING FINISHING CODE TO FOLLOW THAT OF FLOOR FINISHING. SKIRTING HEIGHT TO BE 100mm.

Material Legend_Skirting

1 : 200

Floor Finishes	
Key Value	Description
GS080CH01	MIN. 25mm THK. PROPRIETARY C/S SCREED W/ HARDENER LAID TO FALL WITH TROWELLED SMOOTH FINISH & OVERALL 50mm THK.
GS080FF04	300x300x30mm THK. PRECAST CONCRETE TILES BEDDED ON 25mm THK. C/S SCREED
GS170SS01	3mm THK. S.S. TRIM (SATIN) (GRADE 316)
GS180CS01	PROPRIETARY HEAVY DUTY EPOXY FLOORING SYSTEM, 3mm THK. ON MIN. 50mm THK. PROPRIETARY C/S SCREED STEEL TROWELED SMOOTH FINISH W/ HARDENER
GS180CS02	PROPRIETARY HEAVY DUTY EPOXY FLOORING SYSTEM, 3mm THK. ON MIN. 25mm THK. PROPRIETARY C/S SCREED STEEL TROWELED SMOOTH FINISH W/ HARDENER AND CEMENTITIOUS WATERPROOF SYSTEM (UPTURN 300mm AFFL), LAID TO FALL, OVERALL 25-100mm THK.
GS180CS03	50mm THK. C/S SCREED WITH NON-METALLIC FLOOR HARDENER TROWELLED SMOOTH FINISH, 1 COAT OF POLYURETHANE SEALER, 2 COATS OF EPOXY BASED PAINT AND DUST PROOFING COATING
GS180CS04	PROPRIETARY CARPARK DECKING SYSTEM CONSISTING OF HEAVY DUTY SCREED TROWELLED FINISH TO RECEIVE EPOXY RESIN COATING SYSTEM
GS180CS05	PROPRIETARY CARPARK DECKING SYSTEM CONSISTING OF HEAVY DUTY SCREED TROWELLED FINISH TO RECEIVE EPOXY POLYURETHANE COATING SYSTEM, WITH CEMENTITIOUS WATERPROOF SYSTEM (UPTURN 300mm AFFL)
GS180PF01	50mm THK. HEAVY DUTY POLYURETHANE HYBRID FLOORING SYSTEM "MASTER BUILDERS SOLUTIONS" UCRETE UD200 ON C/S SCREED
GS180PF03	50mm THK. HEAVY DUTY POLYURETHANE HYBRID FLOORING SYSTEM "MASTER BUILDERS SOLUTIONS" UCRETE UD200 ON C/S SCREED WITH CEMENTITIOUS WATERPROOF SYSTEM (UPTURN 300mm AFFL)
GS180PF04	50mm THK. HEAVY DUTY POLYURETHANE HYBRID FLOORING SYSTEM "MASTER BUILDERS SOLUTIONS" UCRETE UD200 ON C/S SCREED WITH CEMENTITIOUS WATERPROOF SYSTEM (UPTURN 1100mm AFFL)
GS180PF05	50mm THK. HEAVY DUTY POLYURETHANE HYBRID FLOORING SYSTEM "MASTER BUILDERS SOLUTIONS" UCRETE UD200 ON C/S SCREED WITH CEMENTITIOUS WATERPROOF SYSTEM (UPTURN 1800mm AFFL)
GS180PF06	50mm THK. HEAVY DUTY POLYURETHANE HYBRID FLOORING SYSTEM "MASTER BUILDERS SOLUTIONS" UCRETE UD200 ON C/S SCREED WITH CEMENTITIOUS WATERPROOF SYSTEM (UPTURN 3050mm AFFL)
GS180TL01	600x1200x10mm THK. HOMOGENEOUS TILE "ARIOSTEA" PIETRE NATURALI HIGH TECH SERIES (COLOUR: ARDESIA ANTRACITE, STRUTTURATO, SHADE VARIATION:V2) THROUGH BODY WITH "ACTIVE" ANTI-BACTERIAL PROPERTY ON C/S SCREED FIXING WITH APPROVED PROPRIETARY ADHESIVE AND POINTING WITH COLOURED GROUTING (R11) OVERALL 50mm THK. (WITH 2 GROOVE LINES FOR STEP NOSING)
GS180TL02	600x1200x10mm THK. HOMOGENEOUS TILE "ARIOSTEA" PIETRE NATURALI HIGH TECH SERIES (COLOUR: ARDESIA ANTRACITE, SEMI-MATT, SHADE VARIATION:V2) THROUGH BODY WITH "ACTIVE" ANTI-BACTERIAL PROPERTY ON C/S SCREED FIXING WITH APPROVED PROPRIETARY ADHESIVE AND POINTING WITH COLOURED GROUTING (R10) OVERALL 50mm THK. (WITH 2 GROOVE LINES FOR STEP NOSING)
GS180TL05	600x300x10mm THK. HOMOGENEOUS TILE "ARIOSTEA" PIETRE NATURALI HIGH TECH SERIES (COLOUR: CADAPPA BLACK, SEMI-MATT, SHADE VARIATION:V2) THROUGH BODY WITH "ACTIVE" ANTI-BACTERIAL PROPERTY ON C/S SCREED FIXING WITH APPROVED PROPRIETARY ADHESIVE AND POINTING WITH COLOURED GROUTING WITH CEMENTITIOUS WATERPROOF SYSTEM (UPTURN 300mm AFFL FOR TOILET & WET AREA) (R10) OVERALL 50mm THK.
GS180TL06	600x300x10mm THK. HOMOGENEOUS TILE "ARIOSTEA" PIETRE NATURALI HIGH TECH SERIES (COLOUR: CADAPPA BLACK STRUTTURATO, SHADE VARIATION:V2) THROUGH BODY WITH "ACTIVE" ANTI-BACTERIAL PROPERTY ON C/S SCREED FIXING WITH APPROVED PROPRIETARY ADHESIVE AND POINTING WITH COLOURED GROUTING WITH CEMENTITIOUS WATERPROOF SYSTEM (UPTURN 1800mm AFFL FOR SHOWER AREA) (R11) OVERALL 50mm THK.
GS180TL08	300x600x10mm THK. HOMOGENEOUS TILE "ARIOSTEA" PIETRE NATURALI HIGH TECH SERIES (COLOUR: BASALTO GRIGIO STRUTTURATO, SHADE VARIATION:V3) THROUGH BODY WITH "ACTIVE" ANTI-BACTERIAL PROPERTY ON C/S SCREED WITH APPROVED PROPRIETARY ADHESIVE SYSTEM AND POINTING WITH COLOURED GROUTING AND WITH CEMENTITIOUS WATERPROOF SYSTEM (UPTURN 300mm AFFL FOR WET AREA ONLY) (R11) OVERALL 50mm THK.
GS180TL11	300x300x12mm THK. NON-SLIP QUARRY FLOOR TILE ON C/S SCREED LAID TO FALL (MIN. 25mm THK) OVERALL 50mm THK. WITH CEMENTITIOUS WATERPROOF SYSTEM (UPTURN 300mm AFFL)
GS180IW03	100mm THK. INSULATION PANEL ON 25mm THK. C/S SCREEDING WITH CEMENTITIOUS WATERPROOF SYSTEM. LIGHT WEIGHT CONCRETE SLAB TO BE SITTING ON TOP OF THE INSULATION PANEL. C/S SCREED LAID TO FALL 1:100 ON LIGHT WEIGHT CONCRETE SLAB
GS180VS01	4mm THK. CHEMICAL RESISTANT HOMOGENEOUS FULLY FLEXIBLE FOAM BACKED VINYL FLOORING WITH SELF COVING BONDED ON 10mm THK. SELF-SMOOTHING SCREED AND LAID ON C/S SCREED WITH WATERPROOF MEMBRANE (UPTURN 300mm AFFL FOR WET AREA ONLY), OVERALL 50mm THK.
GS180VS02	4mm THK. CHEMICAL RESISTANT HOMOGENEOUS FULLY FLEXIBLE FOAM BACKED VINYL FLOORING BONDED ON RAISED FLOOR PANEL SYSTEM, OVERALL 350mm THK.

Material Legend_Floor

1 : 200

NOTES

1. ALL FLOOR FINISHING OF P.D., WORKSTATION SERVICES MAINTENANCE SPACE ARE 50mm THK. HEAVY DUTY POLYURETHANE RESIN FLOOR SYSTEM ON 1:3 C/S SCREEDING.

2. WALL AND CEILING FINISHING OF P.D., WORKSTATION SERVICES MAINTENANCE SPACE ARE VOC FREE ANTI-MOULD ACRYLIC EMULSION PAINT ON-OFF FORM CONCRETE.

3. ALL EXPOSED SURFACE OF G.M.S. WORK TO BE PAINTED WITH SYNTHETIC PAINT REFER CURRENT GENERAL SPECIFICATION.

4. ALL S.S. METAL WORK TO BE IN GRADE 316 SATIN FINISH EXCEPT THOSE OTHERWISE STATED.

5. APPLY APPROVED WOOD PRESERVATIVE TO ALL UNEXPOSED SURFACES OF TIMBER IN ACCORDANCE TO CURRENT GENERAL SPECIFICATION. ALL EXPOSED SURFACE OF CARPENTRY AND JOINERY WORK TO BE APPLIED W/ WOOD PAINT WITHOUT COLOUR EXCEPT THOSE OTHERWISE STATED, DETAIL REF. TABLE OF GENERAL FINISH

6. PROPRIETARY WATERPROOF MEMBRANE SHALL BE : TYPE 'B1' LIQUID APPLIED MATERIAL AS SPECIFIED IN CLAUSE 12.100 OF GENERAL SPECIFICATION FOR BUILDING 2017 EDITION AND LAID STRICTLY IN ACCORDANCE WITH MANUFACTURERS / SPECIALIST CONTRACTORS SPECIFICATION & RECOMMENDATIONS.

a	01 / 2018	ADDENDUM No.1 1. REVISION AS CLOUDED	SA	
			PA	

no.	date	description	initial
-----	------	-------------	---------

REVISION

	name	date
designed		11/2017
drawn		11/2017
checked		11/2017

approved		
Chief Architect	ORIGINAL SIGNED	11/2017
Senior Architect	ORIGINAL SIGNED	11/2017
Project Architect	ORIGINAL SIGNED	11/2017
	signed	date

contract no.

file no. ASD 51/8216/MX/DH/080

project no. 020 NB

contract

drawing title

SCHEDULE & DETAILS OF INTERNAL FINISHES (SHEET 1 OF 7)

drawing no.	scale
-------------	-------

AB/8216/CA001a

1 : 200

office